Q 50-100 | Bitumen UBC / Bitumen UBC Aerosol

Characteristics

50-100 Bitumen UBS black is a durable corrosion protection based on wax/bitumen for floor pans, entry sections and wheel houses and so on. Excellent sound deadening properties, outstanding adhesion, elastic, non-sticking, high abrasion resistance and good resistance to de-icing salt.

50-100 Bitumen UBC **Aerosol** is an elastic and durable rubber-bitumen based underbody protection. Provides a long-term protection against water, salt, corrosion on corners, edges or for repair work.

Physical Characteristics

24 month

500 ml: 2004/42/IIB(e)(840)<515
1 kg: 2004/42/IIB(e)(840)<840

Application 500 ml Aerosol

cleaning

shake well for 2 min

25 cm - 30 cm

clean valve

Application 1 kg

cleaning

5 - 10 mm
4 - 6 bar

1 - 2

5 - 8 min

500 - 1000 µm

Consumption: 1 - 2 m²/l

Drying

500 ml Aerosol — Set to touch: 5 h

1 kg — Set to touch: 2 - 4 h

Processing tips

The floor pan must be cleaned thoroughly. It must be dry, free from dust, grease, oil and rust.
Old non-adherent underbody coating must be removed.
Do not spray on engine, transmission, sump, cardan shaft, exhaust pipes, axles, springs, shock absorbers, brake cables, grease nipples etc., mask this parts before!

Storage

Store the product in a ventilated place. Keep away from direct exposure to sunlight.
Keep between +15°C and 25°C.

Safety

For more informations check the safety data sheet.

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products.
Copyright: ColorCompany GmbH, all rights reserved.

Version: 25-03-2026

ColorCompany GmbH • Kadener Straße 9 • D-25486 Alveslohe, Germany
+49 (0) 4192 89142 0 • www.color-company.com • info@color-company.com