Q 50-105 | Brushable UBC Bitumen

Characteristics

50-105 Bitumen UBS brushable is a highly resistant coating for floor pans, wheel houses and so on. It provides a durable protection against corrosion, de-icing salt and stone-chip. Excellent adhesion, shock- and scratch-resistant, long-term flexible film, good sound deadening properties, non-drip application.

Physical Characteristics

COLOR ■

VOC 2004/42/IIB(e)(840)<840

12 M 24 month

Application

cleaning

mind. + 10°C

ca. 3mm

Consumption: 1 - 2 m^2/l

Drying

20°C 3,5 h

Processing tips

The floor pan must be cleaned thoroughly. It must be dry, free from dust, grease, oil and rust.
Old non-adherent underbody coating must be removed.
Do not apply on engin, transmission, sump, cardan shaft, exhaust pipes, axles, springs, shock absorber, brake cables, grease nipples, etc..

Storage

Store the product in a ventilated place. Keep away from direct exposure to sunlight.
Keep between +10°C und 25°C.

Safety

For more informations check the safety data sheet.

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products.
Copyright: ColorCompany GmbH, all rights reserved.

Version: 25-03-2026

ColorCompany GmbH • Kadener Straße 9 • D-25486 Alveslohe, Germany
+49 (0) 4192 89142 0 • www.color-company.com • info@color-company.com