Q 50-150 | Cavity Wax / Cavity Wax Aerosol

Characteristics

50-150 Cavity Wax is a protective coat with corrosion protection which is based on special waxes to conserve and seal car body cavities. Thanks to its penetrating properties moisture is displaced also in corners and seams. No dripping or running.

Physical Characteristics

COLOR

12 M 24 month

VOC 500 ml: 2004/42/IIB(e)(840)<550
1 kg: 2004/42/IIB(e)(840)<448

Application 500 ml Aerosol

cleaning

shake well for 2 min

40 µm

clean valve

Application 1 kg

cleaning

5 - 10 mm
4 - 6 bar

1 - 2

Drying

20°C

500 ml	30 - 60 min
1 kg	30 - 60 min

Processing tips

Do not spray on the motor, gears, brakes etc.

Storage

Store the product in a ventilated place. Keep away from direct exposure to sunlight.
Keep between +15°C and 25°C.

Safety

For more informations check the safety data sheet.

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products.
Copyright: ColorCompany GmbH, all rights reserved.

Version: 26-03-2026

ColorCompany GmbH • Kadener Straße 9 • D-25486 Alveslohe, Germany
+49 (0) 4192 89142 0 • www.color-company.com • info@color-company.com